

Domino ASH Vulcano

cut / raw

Collection
DOMINO

Article Nr: EDDOGKR040020009



highest stress class) must be noted.

Extremely robust (suitable for ateliers and commercial properties!). Can also be used for raised floors.

INSTALLATION:

Important! Installation should only be carried out by experts and the installation guidelines must be observed.

The maximum relative humidity of cement screed may not exceed 2 CM% (with underfloor heating 1.8 CM %). Additionally, the appropriate adhesive tensile strength (min. 1.2 N/mm² -

Measurements

Length	400 mm
Width	200 mm
Thickness	9 mm

Specification

Surface	cut
Lye	
Oil	raw



Made from specially heat treated ash (without chemical additives), assembled in compact ready-to-install elements of end-grain blocks (40 x 40 mm). These are held together on a parquet net. Isolated stress cracks and expansion gaps (e.g. due to climatic changes) are possible in the elements. These do not however influence the functionality of the floor (strength and stress bearing properties) in any way.

mafi Domino floors are not oiled on the production side, but must be oiled on site after installation. Therefore, Domino floors can only be ordered in unfinished form. The final appearance can then be achieved with the appropriate mafi wood flooring oils.

Natural wooden floors made in AUSTRIA

mafi Naturholzboden GmbH

Utzweihstrasse 21+25 · A 5212 Schneegattern · +43 · [0]7746 2711 - 0 · office@mafi.com · www.mafi.com

mafi
: walk on art

Domino ASH Vulcano

cut / raw

Collection
DOMINO



Article Nr: EDDOGKR040020009

References



mafi flagshipstore Graz

8010 Graz

Austria



Restaurant & Vinotheque Magazin:

5020 Salzburg

Austria

Natural wooden floors made in AUSTRIA

mafi Naturholzboden GmbH

Utzweihstrasse 21+25 · A 5212 Schneegattern +43 · [0]7746 2711 - 0 · office@mafi.com · www.mafi.com

mafi
: walk on art